



T ARGET SERIES



T1220B

12" 2-Way Passive Trapezoidal Upright w/UltraBass Upgrade

Specifications:

Frequency Response: 70Hz–16kHz
Cont. Program: 400W
Nominal Impedance: 8 ohms
Sensitivity (1W/1M): 99dB
Max Peak SPL: 128 dB@1meter
Coverage: 120° H x 60° V
X-Over Frequency: 3kHz
Dims: 24"H x 15"W x 16"D
Net Weight: 62 lbs.

Features:

3/4" Multi-ply Construction,
Powder Coated Steel Grill,
Pole Mount Socket
Cast Frame Woofer, 1" Exit Compression
Driver, HF Protection, 2 x Neutrik Speakon™
Connectors, Handles & Corners



T1222B


12" 2-Way Passive Stage Monitor w/UltraBass Upgrade

Specifications:

Frequency Response: 70Hz–16kHz
Cont. Program: 400W
Nominal Impedance: 8 ohms
Sensitivity (1W/1M): 99dB
Max Peak SPL: 128 dB@1meter
Coverage: 120° H x 60° V
X-Over Frequency: 3kHz
Dims: 21"H x 15"W x 14.5"D
Net Weight: 57 lbs.

Features:

3/4" Multi-ply Construction,
Powder Coated Steel Grill,
Cast Frame Woofer, 1" Exit Compression
Driver, HF Protection, 2 x Neutrik Speakon™
Connectors, Handles & Corners



T1540B

15" 2-Way Passive Trapezoidal Upright

Specifications:

Frequency Response: 50Hz–16kHz
Cont. Program: 800W
Nominal Impedance: 8 ohms
Sensitivity (1W/1M): 99dB
Max Peak SPL: 131dB@1meter
Coverage: 90° H x 40° V
X-Over Frequency: 2kHz
Dims: 27"H x 18"W x 16.5"D
Net Weight: 76 lbs.

Features:

3/4" Multi-ply Construction,
Powder Coated Steel Grill,
Pole Mount Socket
Cast Frame Woofer, 1" Exit Compression
Driver, HF Protection, 2 x Neutrik Speakon™
Connectors, Handles & Corners



T1522B

15" 2-Way Passive Stage Monitor

Specifications:

Frequency Response: 50Hz–16kHz
Cont. Program: 800W
Nominal Impedance: 8 ohms
Sensitivity (1W/1M): 99dB
Max Peak SPL: 131 dB@1meter
Coverage: 120° H x 60° V
X-Over Frequency: 3kHz
Dims: 23.75"H x 17.5"W x 18.8"D
Net Weight: 67 lbs.

Features:

3/4" Multi-ply Construction,
Powder Coated Steel Grill,
Cast Frame Woofer, 1" Exit Compression
Driver, HF Protection, 2 x Neutrik Speakon™
Connectors, Handles & Corners



T1840B

Single 18" Subwoofer System

Specifications:

Frequency Response: 45Hz–500Hz
Cont. Program: 800W
Nominal Impedance: 8 ohms
Sensitivity (1W/1M): 99dB
Max Peak SPL: 131 dB@1meter
X-Over Frequency: 100Hz
Dims: 25.25"H x 22"W x 19"D
Net Weight: 81 lbs

Features:

3/4" Multi-ply Construction,
Powder Coated Steel Grill,
Pole Mount Socket
Cast Frame Woofer, 2 x Neutrik Speakon™
NL4 Connectors, Handles & Corners



T2840B

Dual 18" Subwoofer System

Specifications:

Frequency Response: 30Hz–300Hz
Cont. Program: 1600W
Nominal Impedance: 4 ohms
Sensitivity (1W/1M): 99dB
Max Peak SPL: 130 dB@1meter
Recommended X-Over Freq.: 100Hz
Dims: 45"H x 22.5"W x 26.75"D
Net Weight: 165 lbs

Features:

3/4" Multi-ply Construction,
Powder Coated Steel Grill,
Cast Frame Woofer, 2 x Neutrik Speakon™
NL4 Connectors, Handles & Corners, & Wheels

TARGET SERIES

The Next Phase In Loudspeaker Technology™

www.pas-toc.com

E-mail: Sales@pas-toc.com