



The Next Phase
In Loudspeaker
Technology

Power Response



Specifications

Specifications	PR12M	PR15M	PR12T	PR15T	PR18B
Frequency Response	70Hz-20kHz	60Hz-20kHz	60Hz-20kHz	50Hz-20kHz	40Hz-300Hz
Continuous Program	300 Watts	350 Watts	300 Watts	350 Watts	800 Watts
Nominal Impedance	8	8	8	8	4
Sensitivity(1w/1m)	98 dB	99 dB	98 dB	99 db	99 dB
Max Peak SPL	126 dB	127 dB	126 dB	127 dB	131 dB
Nominal Coverage Angles	60° h x 60° w	60° h x 60° w	90° h x 40° w	90° h x 40° w	
Crossover Frequency	3 kHz	3 kHz	3 kHz	3 kHz	100 Hz
Height	14¾"	18¼"	24½"	28½"	34"
Width	19¼"	23¼"	15¼"	18¼"	21½"
Depth	12¼"	15"	16½"	16"	24"
Net Weight	35 lbs.	47 lbs.	47 lbs.	57 lbs.	90 lbs.

Professional Audio Systems

2270 Cosmos Court, Carlsbad, CA 92009, USA

Voice: (760) 431-9924 Fax: (760) 431-9496 Web: www.pas-toc.com

E-Mail: info@pas-toc.com